



### Ordering Information

C108 - 26 F T B 0 1

- Series No. 1 - 3.08mm Footprint
- No. of Pins: 2 - 9.4mm Footprint
- 15,26,44,62
- Gender: M - Male
- F - Female
- Shell Plating: C - Chromeplated
- T - Tinned
- Screw Type: 0 - #4-40, W/O Rivet
- 1 - #4-40, Rivet
- Insulator Colour: B - Blue
- K - Black
- W - White

# C108 Series

## D-Sub H.D. Right Angle Type

### Specifications:

Contact Resistance: 30mΩ @ 100mA DC  
 Insulator Resistance: 1000MΩmin. @ 500V DC  
 Current Rating: 3AMP  
 Voltage: 1000V AC For 1 minute  
 Operating Temperature: -55°C~+105°C  
 Contact: Brass or Phosphor Bronze, Stamped  
 Housing: PBT, UL94V-0

Positions	A	B	C	D	E
15	17.78	24.99	31.04	16.33	2.29
26	26.15	33.32	39.24	24.66	2.29
44	39.94	47.04	53.04	38.66	2.29
62	56.56	63.50	69.62	54.84	2.41

  

Footprint	F	G	H
1	3.08	5.08	14.45
2	9.4	10.89	22.20

